

Appln. No. 10/773,987; filed 02/05/04

Atty. Docket No.: 70030756-2

RECEIVED
CENTRAL FAX CENTER

OCT 10 2006

Claim Amendment

1. (Currently Amended) An apparatus of generating an output code stream, comprising:
 - a first bit repeater to repeat an incoming code stream;
 - a second bit repeater to repeat a first parity bit stream of generated from the incoming code stream;
 - a third bit repeater to repeat a second parity bit stream of generated from the incoming code stream;
 - a multiplexer coupled to the first, second, and third bit repeaters to combine the repeated incoming code stream, the repeated first parity bit stream, and the repeated second parity bit stream to generate the output code stream that is optimally-repeated from the incoming code stream and its the parity bit streams;
 - a control module coupled to the first, second, and third repeaters to provide each of the repeaters with an individually set repeating rate.
2. (Original) The apparatus of claim 1, further comprising
 - a first parity generator to generate the first parity bit stream;
 - an interleaving module to interleave the incoming code stream;
 - a second parity generator coupled to the interleaving module to generate the second parity bit stream based on the interleaved incoming code stream.
3. (Original) The apparatus of claim 2, wherein each of the first and

Appln. No. 10/773,987; Filed 02/05/04

Atty. Docket No.: 70030756-2

second parity generator is a recursive systematic convolutional code encoder.

4. (Canceled).

⁴/₅. (Currently Amended). The apparatus of ~~claim 4~~ ¹/₅ ~~claim 5~~, wherein the repeating rate of each of the repeaters is set by the control module such that the transmission rate of the output code stream matches a transmission rate of a communication channel that transmits the output code stream to a decoder while the output code stream is optimally-repeated.

⁵/₆. (Currently Amended) A method of generating an optimally-repeated output code from an incoming code, comprising
repeating the incoming code, a first parity bit stream of generated from
the incoming code, and a second parity bit stream of generated from the
incoming code individually and separately from each other such that optimal performance is obtained when the repeated incoming code, the repeated first parity bit stream, and the repeated second parity bit stream are combined to generate the output code;

combining the repeated incoming code, the repeated first parity bit stream, and the repeated second parity bit stream to generate the output code;
determining the repeating rate for each of the incoming code, the first parity bit stream, and the second parity bit stream individually and separately such that the transmission rate of the output code stream matches a transmission rate of a communication channel that transmits the output code stream to a decoder while the output code stream is optimally-repeated.

Appln. No. 10/773,987, Filed 02/05/04

Atty. Docket No.: 70030756-2

⁶
7. (Original) The method of claim ⁵~~6~~, further comprising
generating the first parity bit stream by a first recursive convolutional
code encoder;
interleaving the incoming code; and
generating the second parity bit stream from the interleaved incoming
code by a second recursive convolutional code encoder.

8. (Canceled).